

GLOWLINE



Description

The GlowLine is a versatile and flexible lighting solution designed to add continuous, seamless illumination to any space. Its durable, weather resistant construction and uniform glow make it perfect for both indoor and outdoor applications. With energy efficient LEDs and a wide range of color options, the GlowLine enhances ambiance, accentuates architectural features, and delivers long lasting performance.

Product Benefits

Up to 70% in Energy Saving
Weatherproof & Durable with IP65-rated
Flexible Design with 1m Intervals
Low-heat Output Ensures Long-term Safety
Available in Six Vibrant Colors

Application Areas

Patios / Gardens / Stairways
Commercial Spaces / Living Spaces
Restaurants / Hospitality
Pathways / Pool Areas

Product Data

General Information	
Driver Included:	Yes
Lifespan:	15,000 hours @ L70
Warranty:	Check Warranty
Luminaire Performance	
Power Consumption (per meter):	5-6W, 7-8W
Diameter (mm):	6.8, 8
Luminous Efficacy (rated per meter):	390 lm, 550 lm
Correlated Color Temperature:	3000K, 4000K, 6500K, Green, Blue, Red, Pink
Color Rendering Index (CRI):	>70

Operating and Electrical	
Input Voltage:	AC185-240V
Line Frequency:	50 or 60 Hz
Power Factor (Fraction):	>0.9
Temperature	
Operating Temperature:	-10°C – 40°C
Controls and Dimming	
Controls:	On/Off



LIGHTS

PRODUCT SPECIFICATION

Mechanical and Housing

PCB Material:	Copper
Housing Material:	PVC
Optical Cover Material:	PVC
Installation:	Surface Mounted, Wall Mounted

Compliance and Certifications

Ingress Protection Code:	IP65
--------------------------	------

Dimensions

Power Consumption:	5-6W	7-8W
Diameter (mm):	6.8	8
Net Weight (kg):	2.75	3.75
Length (m):	50	

Head Office:

192-Y Block, Commercial Area, Phase III, DHA Lahore, Pakistan.

Sales Office:

120-Y Block, Commercial Area, Phase III, DHA Lahore, Pakistan.



MRK/PM/PS/RPGL/25/01